


 Kit Accessory Ø50 TA.0174.0000
 incluso / included

Powerful Three-phase industrial vacuum cleaner equipped with side channel blower for continuous work, maintenance free.
 Suitable for wet, dry and dust applications at the same time.
 Detachable container with possibility to use disposable bags.
 Large filter surface with integrated filter cleaning system.

Aspiratore industriale trifase dotato di potente turbina a canale laterale per il servizio continuativo.

*Prestazioni costanti senza necessità di manutenzioni.
 Aspirazione simultanea di polveri, liquidi, solidi.
 Contenitore a sgancio con possibilità di insaccamento.
 Filtro di ampia superficie con sistema di pulizia manuale integrato.*

| TECHNICAL DATA / DATI TECNICI | | FW 3 Infini 2,2kW | FW 3 Infini 4kW |
|---|---------------------|-------------------|-----------------|
| Voltage / Tensione | V - Hz | 400 - 50 3~ | 400 - 50 3~ |
| Power / Potenza | kW | 2,2 | 4 |
| Water Lift max. / Depressione max. | mm.H ₂ O | 3.000 | 3.200 |
| Air Flow max. / Portata d'aria max. | M ³ /h | 320 | 420 |
| Filter surface / Superficie filtrante | Cm ² | 20.000 | |
| Filter type / Tipo di filtro | | Star / Tasche | |
| Ø filter / Ø filtro | mm. | 420 | |
| Media, class / Media, classe (IEC 60335-2-69) ² | | Polyester - L | |
| Tank capacity / Capacità contenitore | Lt. | 65/100 | |
| Ø Suction inlet / Ø Bocchettone | mm. | 80 | |
| Noise level / Rumorosità (EN ISO 3744) | dB(A) | 74 | 74 |
| Dimensions / Dimensioni | cm. | 108x62x137h | |
| Weight / Peso | kg. | 105 | 120 |

| Standard version price / Prezzo versioni standard | |
|---|--|
| FW 3 Infini 2,2kW | |
| FW 3 Infini 4kW | |
| FW 3 Infini 2,2kW Lt. 100 - NEW | |
| FW 3 Infini 4kW Lt. 100 - NEW | |

| Recommended accessory / Accessori consigliati | | | |
|--|--|--------------|--|
| Ø50 Rubber cone nozzle / Tronco conico in gomma |  | TA.0014.0000 | |
| Ø50 Double bend / Doppia curva |  | SL.0170.7016 | |
| Ø50 Wheeled floor brush / Spazzola pavimento con ruote |  | TA.0141.0000 | |
| Ø50 Wheeled squeegee / Spazzola ventosa con ruote |  | TA.0132.0000 | |

Optionals / Opzioni

| | | |
|---|----------|--|
| Pressure relief valve / Valvola limitatrice di vuoto | PRF | |
| Antistatic Class M filter / Filtro Classe M Antistatico | M ANT | |
| PTFE Coated Antistatic Class M filter / Filtro Classe M PTFE Antistatico | PTFE ANT | |
| Class M Teflon filter Hydro-Oleophobic / Filtro Classe M Teflonato Idro-oleofobico | TF OWR | |
| Nomex -heat resistant filter up to 200°C / Filtro resistente al calore fino a 200°C | N | |
| H14 Absolute filter kit / Filtro assoluto Hepa H14 - 26.500cm ² with 99,995% efficiency at 0,18µ | H14 | |
| Stainless steel 65lt. collection tank AISI 304 / Contenitore 65lt. in acciaio inox AISI 304 | X | |
| Stainless steel 100lt. collection tank AISI 304 / Contenitore 100lt. in acciaio inox AISI 304 | X | |
| Stainless steel 65lt. tank and filter chamber AISI 304 / Contenitore 65lt. e camera in acciaio inox AISI 304 | XX | |
| Stainless steel 100lt. tank and filter chamber AISI 304 / Contenitore 100lt. e camera in acciaio inox AISI 304 | XX | |
| Earth grounding / Messa a terra | EG | |
| Remote Control / Avviamento locale remoto | RC | |